

sensohive



Orbit 3

Wireless temperature and humidity sensor

The wireless temperature and humidity sensor measures the air temperature and humidity in the center hole in the front of the sensor.

Between the sensor element and air around the sensor is a IP67 filter to cover and protect the sensor element in best possible way.

The sensor transmits data using the Sigfox-network, so you do not have to make any local installation of Wi-Fi, gateways/masterbox or similar setup.

www.sensohive.com/sensors/orbit3

Date: 25-07-2018 // Version: 1.3.1 // English

Information in this datasheet is based on specifications believed correct at the time of publication. The right is reserved to make changes as design and general improvements are introduced.

Features

- No use of local gateway or installations
- $\pm 0,3$ °C and $\pm 2\%$ RH accuracy
- Touch functionality
- Long battery lifetime
- Robust design

Advantages

- Easy installation and activation
- Versatile use
- Maintenance free
- Low total cost of ownership
- Globally connected ¹

Configuration Options

The Orbit 3 Sensor comes preconfigured with default settings. The Orbit 3 will as standard measure every 7.5 min. and transmit data to the cloud every 30 min.

These settings will be possible to change through the Sensohive App. The sensor will update the settings at least once a week in auto-mode or force updated through tapping 4 times on the sensor. Then the sensor will enter an update mode, where all settings will be updated to the settings you have set in the Sensohive App for the specific sensor.

Through the Sensohive App it is possible to change following settings:

- Sample rate
- Transmitting rate
- Warning zone
- Alarm zone

¹Global connection refers to the area covered by Sigfox. Local requirements, legislation, and infrastructures can affect the network availability. Updated outdoor coverage: www.sigfox.com

Specifications

Sensors	Temperature (Internal) Humidity (Internal) Accelerometer, 3-axis
Tolerances	± 0.3 °C and $\pm 2\%$ RH
Resolution	0.1 and 0.5
Measurement Range	-30 to 50 °C
Operating Temperature	-30 to 50 °C
Operating Humidity	0 to 100% RH ²
Measurement Interval	Every 7.5 min (adjustable)
Transmission Interval	Every 30 min (adjustable)
Battery Type	Li-SOCl ₂ , not replaceable 3.6 V 5.400 mAh
Battery Lifetime	Up to 10 years ³
Tap Functionality	Yes
Network	Sigfox
Radio Zones	RC1, RC2, RC4 ⁴
Material Enclosure	ABS plastic (FDA approved)
Dimensions	75 x 23 mm (Ø x H)
Weight	82g
Certifications	CE Sigfox Ready, Class 0 (Best) Radio Equipment Directive (RED) RoHS

² Long-term exposure to conditions outside normal humidity range (20-80% RH) and prolonged exposure to extreme conditions may accelerate ageing.

³ Battery life depends on mode, operating temperature, and frequency of measurements and transmissions. Standard configuration gives a lifetime of 4-5 years (estimated based on tests and simulations).

⁴ RC1 and RC2 are Sigfox Ready certified with Class 0. RC4 is pending certification and are currently available as samples.

